

# PERFORMER LABORATORY FREEZERS (-25°C to -10°C)

**LABEC** supplies 6 models in the **Performer Range of Laboratory Freezers** ranging from 300 litres to 1400 litres in one, two and three door configurations.

The glass door models are fitted with tempered thermo double glazed glass doors for easy visibility and convenience and the 374 litre/900 litre and 1400 litre models are available in either glass or solid door.

The Labec laboratory freezers are designed for general purpose storage of non-critical products. The larger models utilise CFC urethane insulation between the surfaces. Lockable swivel castors fitted to the base make moving the refrigerator into place easy and general cleaning more accessible.

All models feature self closing glass doors (with internal lighting) or solid door(s). Adjustable open wire white plastic coated full width shelves which are easily removable.

A hermetically sealed refrigeration system utilizing CFC-Free refrigerant provides controlled temperature conditions within all models using a digital temperature controller with Hi/Lo temperature memory. Power requirements for all models are 10A 240Volts AC 50Hz power supply.

Options Available - voltage fluctuation protection, additional shelving, lockable doors, stainless steel interior (some models only).



900 Litre Model



1400 Litre Model

Serving the Scientific, Medical and Research industries since 1945

**LABEC**

**LABEC**

Laboratory Equipment Pty Ltd

Laboratory Equipment Pty Ltd  
email: [sales@labec.com.au](mailto:sales@labec.com.au)  
Ph: 02 9560 2811 • Fax: 02 9560 6131  
[www.labec.com.au](http://www.labec.com.au)

## SPECIFICATIONS

# PERFORMER LABORATORY FREEZERS (-25°C to -10°C)

Model	PLFSD300	PLFSD600	PLFSD900	PLFSD1400
	PLFGD300	PLFGD600	PLFGD900	
Capacity (litres)	300	600	900	1400
Int. Dim. (cm) H x W x D	150 x 45 x 40	122 x 68 x 66	122 x 100 x 66	155 x 124 x 65
Ext. Dim. (cm) H x W x D	184 x 60 x 64	202 x 76 x 76	202 x 110 x 76	202 x 164 x 76
Temperature Controller	Digital Temperature Controller			
Temp. Min	-10°C			
Temp. Max	-24°C			
Refrigerant	134a CFC Free			
Number of Doors	1		2	3
Door Material	Glass or Solid ( GD- glass/ SD-solid)			
Standard Shelving	6 x fixed shelves	5 x adjustable shelves	10 x adjustable shelves	15 x adjustable shelves
Castors	Standard			
Options	Additional shelves, BMS monitoring, temperature monitoring and logging, glass doors or solid doors, stainless steel interior or exterior.			
Power Supply	10AMP/240V/50Hz			
Weight (kg)	85	160	210	330

Serving the Scientific, Medical and Research industries since 1945



Laboratory Equipment Pty Ltd

Laboratory Equipment Pty Ltd

email: sales@labec.com.au

Ph: 02 9560 2811 • Fax: 02 9560 6131

www.labec.com.au