

VACUUM DRYING OVEN

(+200°C) (+300°C) (+400°C)

LABEC Vacuum Oven is manufactured in Australia with high quality stainless steel for easy maintenance and excellent durability. Used where the entire heat-treating process is to take place under vacuum or a precisely controlled atmospheres.

An iconel element inside the vacuum chamber either wall or centre mounted with valves for the vacuum, bleed and purge of the oven chamber.

Available in cylindrical or square chamber up to 100 litres capacity and a temperature range of Ambient +5°C up to 150°C, 300°C or 400°C.

An analogue gauge up to -100KPA displays chamber pressure and a digital microprocessor based PID temperature controller controls the temperature. When optioned the controller can be connected via RS232/RS458 communication ports which can be connected directly to a data logger or computer to collect this information. Software is available for programming and monitoring.

To suit your functionality the addition of options such as a safety toughened glass viewing window for easy viewing, programmable controllers, timers and vacuum pumps are also available.



OTHER STANDARD FEATURES INCLUDE:

- Over temperature thermostat
- RCD/ ELB (earth leakage breaker)
- Type K Thermocouple
- Stainless steel exterior
- Adjustable/removable shelving

Serving the Scientific, Medical and Research industries since 1945

LABEC

LABEC

Laboratory Equipment Pty Ltd

Laboratory Equipment Pty Ltd

email: sales@labec.com.au

Ph: 02 9560 2811 • Fax: 02 9560 6131

www.labec.com.au

SPECIFICATIONS

VACUUM DRYING OVEN (+200°C) (+300°C) (+400°C)

Model	VO1	VO2	VO3	VO4	VO5	VO6
Capacity (litres)	37	45	37	37	100	40
Int. Dim. (cm)	Cylindrical Chamber 33dia x 43depth	Cylindrical Chamber 33dia x 55depth	Cylindrical Chamber 33dia x 43depth	Cylindrical Chamber 33dia x 43depth	Square Chamber 50x50x40	Square Chamber 43x30x30
Ext. Dim. (cm) HxWxD	68x55x58	68x55x66	68x55x58	68x55x58	90x90x71	80x50x50
Temp. Controller	Digital PID Controller					
Temp. Min	Ambient+5°C					
Temp. Max	150°C	150°C	300°C	400°C	200°C, 300°C or 400°C	200°C, 300°C
Temp. Setting Accuracy	0.1°C					
Temp. Fluctuation	+/- 0.2°C					
Temp. Sensor	Type K					
Heating System	Electric Element					
Interior Material	Stainless Steel					
Exterior Material	Stainless Steel					
Shelves	2					
Options	Glass viewing window, vacuum pump, programmable controller, timer, additional shelves.					
Safety Features	Over temperature alarm temperature protection cut off, earth leakage breaker (ELB)					
Power Supply	240V / 50Hz					
Power (W)	1000	1000	2400	2400	3000-7200	2400-6800
Weight (kg)	60	65	78	85	85-125	68

Serving the Scientific, Medical and Research industries since 1945



Laboratory Equipment Pty Ltd

Laboratory Equipment Pty Ltd

email: sales@labec.com.au

Ph: 02 9560 2811 • Fax: 02 9560 6131

www.labec.com.au